

ST-60-C5

Touch Screen



High speed, flexible POS terminal, designed with the power and flexibility to meet the needs of both the retail and hospitality sectors. The ST-60-C5 from TOSHIBA TEC is a real step forward for the hospitality sector, fashion and other retail businesses, who need more than just a POS system.

The ST-60-C5 offers the same successful compact and spill-proof design as its predecessor (ST-60) but with much more power and options. A dual display interface supports a second, customer-facing screen to enable retailers to promote products and services to their customers with a much greater visual impact at the counter.

ST-60-C5



High memory capacity and transaction throughput are key advantages of this brand-new model, which is designed to optimise real-life performance at the Point of Sale. The ST-60-C5 comes as standard with an Intel Celeron™ processor (embedded to give efficiency and reliability), a super fast on-board network adapter (10Base-T/100Base-TX) and impressive memory capacity of 64 MB, which can be increased to 320 MB for reduced paging.

In addition to its power and flexibility, the ST-60-C5 is user-friendly and reliable with low total cost of ownership (TCO).

The ST-60-C5 has been thoroughly tested in severe environments and extreme conditions such as repetitive touching, water spills, screen tilt tests, etc. It has been specifically designed to cater for many demanding applications, including QSR, fine dining, speciality shops...

The super-bright TFT screen can be viewed from almost any angle, which, with the screen tilt angle of 0-90° and smooth touch functionality with optional tone makes the ST-60-C5 one of the easiest-to-use POS terminals on the market.

Powerful Performance

At the heart of the ST-60-C5 is a specially-designed motherboard, which comes as standard with the latest Intel Celeron™ processor, an upgradable 64 MB RAM and a high-speed LAN interface.

TOSHIBA TEC Europe Retail Information Systems European Operations

Austria

Triester Straße 14
2351 Wiener Neudorf
Tel.: +43 (0) 2236 49 766
Fax: +43 (0) 2236 49 794

Belgium

Celideestraat 33 rue de la Célidée
1080 Brussel-Bruxelles
Tel.: +32 (0) 2 410 21 00
Fax: +32 (0) 2 410 68 69

France

23/25, Avenue Jeanne d'Arc
94117 Arcueil Cedex
Tel.: +33 (0) 1 58 07 20 00
Fax: +33 (0) 1 58 07 20 01

Germany

Europark Fichtenhain B15
47807 Krefeld
Tel.: +49 (0) 2151/838-01
Fax: +49 (0) 2151/838-480

Ireland

Unit 11, Naas Road Business Park
Naas Road, Dublin 12
Tel.: +353 (0) 1-450-1511
Fax: +353 (0) 1-450-0683

Portugal

Dr. José Joaquim de Almeida, 2-4º:
Sto Amaro de Oeiras
2780-337 Oeiras
Tel.: +351 21-446-7966
Fax: +351 21-441-5836

Multimedia

The ST-60-C5 its dual screen interface and rich sound capabilities make it ideal for creative retailers who want to benefit from the latest technology advances to increase their sales. In-store promotions, advertising, videos and loyalty scheme communications are all now possible during the POS transaction.

Open and flexible

The ST-60-C5 supports the whole range of Microsoft Windows operating systems, including Windows®98, Windows NT®, Windows®2000 and Windows®XP. As a key member of the OLE POS Committee, TOSHIBA TEC continuously promotes the standardisation of drivers for peripheral devices for the retail market. This standardisation in turn provides the versatility and convenience of application development for VAR and software developers allowing the flexibility to use peripherals from different manufacturers in one system.

CPU	Intel Celeron™ (embedded processor)
RAM	64 MB on board, Max. 320 MB, DIMM x 1
NV-RAM	Option
Cache Memory	128 KB
HDD	2.5" IDE (option), Max. 2 drives
FDD	External FDD (option)
LAN	10BASE-T/100BASE-TX
PCMCIA	Type II x 1 (option)
MCR	Option (track 1, 2 or track 1, 2, 3 or JIS I/II)
Operator Display	12.1" color TFT (active) with touch panel
Customer Display	2 x 20 VFD (option), 12.1" TFT (option)
Interface	RS-232C x 3, Parallel x 1, PC Keyboard, Mouse, Dual screen and sound, USB x 2, Drawer x 2
Power	Autosensing
Dimensions	295 (W) x 350 (D) x 129-343 (H) mm
Weight	8 Kg (excluding options)
Operating temperature	5-35°C

Your TOSHIBA TEC dealer:

Spain

C/ Doctor Esquerdo, 207
28007 Madrid
Tel.: +34 91 502-1590
Fax: +34 91 501-8100

The Netherlands

Maanlander 14E
3824 MP Amersfoort
Tel.: +31 (0) 33 4759456
Fax: +31 (0) 33 4759460

UK

Siskin House, Marlins Meadow
Croxley Business Park
Watford, Herts WD18 8TY
Tel.: +44 (0) 1923 233688
Fax: +44 (0) 1923 233698

TEC Polska Sp. z o.o.

Ul. Marynarska, 21
02-674 Warszawa
Tel.: +48 22 640 48 58
Fax: +48 22 640 48 53

www.toshibatec-eu.com

TEC
TOSHIBA TEC EUROPE
Retail Information Systems